


EssentialsDesigns

Fixation

Construction	Tufted, Level Loop Pile
Face Fibre	100% Milliken-Certified WearOn® Type 6,6 Nylon
Soil Release	Milliguard Plus® for Soil release, liquid repellence
Antimicrobial	Milliken Anti - microbial built-In Protection
Finished Face Weight	410 gsm
Gauge	40 / 10 cm
Rows	52 / 10 cm
Tuft Density	210,000
Finished Pile Height	3.0 mm
Standard Backing	85% Recycled content Polyurethane cushion Available with TractionBack® on request
Nominal Total Thickness	8.4 mm
Tile Size	457.2 x 457.2 mm
Nominal Total Weight	3700 gsm
Tiles per Box	20 (4.17 m ²)



PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Bfl – s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot metal nut BS4790)	Low radius of Char
Use Classification (EN1307)	Class 3 3 Heavy Commercial Use
Static Electricity (ISO 6356)	≤ 2.0 KV, Permanent Conductive Fiber
Impact Sound (ISO 140-8)	34dB
Sound absorption (ISO 354)	0.3 Class D

ENVIRONMENTAL

85% Recycled content cushion backing
12% Recycled content by total product weight
Manufactured using electricity from renewable sources
Carbon Neutral certification
GUT & CRI Green Label Plus certified for indoor air quality
BRE Certification

Design Copyright – Milliken & Company

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending.

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.



Guarantees:

10 year wear guarantee
Lifetime Antistatic guarantee
Latent Defects guarantee

Installation Method:

Brick

