

Juxtapose

Construction	Tufted, Level Loop Pile
Face Fibre	Universal® Fibres Solution-Dyed Type 6,6 Nylon
Antimicrobial	AlphaSan Anti- microbial built-In Protection
Finished Face Weight	690 gsm
Gauge	40.5 / 10 cm
Rows	52 / 10 cm
Tuft Density	210,000
Finished Pile Height	5.0 mm
Standard Backing	Comfort Plus2 85% Recycled Polyurethane cushion Available with TractionBack® on request
Nominal Total Thickness	10.9 mm
Tile Size	457.2 x 457.2 mm
Nominal Total Weight	3990 gsm
Tiles per Box	16 (3.34m ²)



PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Bfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot metal nut BS4790)	Low radius of Char
Use Classification (EN1307)	Class 33 Heavy Commercial Use
Static Electricity (ISO 6356)	≤ 2.0 KV, Permanent Conductive Fibre
Impact Sound (ISO 140-8)	37dB
Sound absorption (ISO 354)	0.35 Class D

ENVIRONMENTAL

14% Recycled content by total product weight
85% Recycled content cushion backing
20% Recycled content yarn
Manufactured using electricity from renewable sources
Carbon Neutral certification
CRI Green Label Plus certified for indoor air quality

Design Copyright - Milliken & Company

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending.

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.



Guarantees:


15 year wear guarantee

Lifetime Antistatic guarantee

Latent Defects guarantee

Installation Method:

Monolithic



Milliken™