


Out of the Shadows

Shadowbox / Scattergraph

Construction	Tufted, Textured Loop Pile
Face Fibre	100% Milliken Certified Nylon 6,6
Stain Repel / Stain Resist / Soil Release	StainSmart®
Antimicrobial	AlphaSan® Built-In Protection
Finished Face Weight	620 g/m ²
Gauge	32 / 10 cm
Rows	46.5 / 10 cm
Tuft Density	148,800
Finished Pile Height	3.0 mm avg.
Standard Backing	ComfortPlus ² 85% Recycled content Polyurethane cushion
	Available with TractionBack® on request
Nominal Total Thickness	10.9 mm
Tile Size	457.2 x 457.2 mm
Nominal Total Weight	4000 gsm
Tiles per Box	16 (3.34 m ²)



PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Cfl – s1
Flammability (Radiant Panel ASTM-E-648)	Class I
Flammability (Hot metal nut BS4790)	Low radius of Char
Use Classification (EN1307)	Class 3,3 Heavy Commercial Use
Static Electricity (ISO 6356)	≤ 2.0 KV, Permanent Conductive Fiber
Impact Sound (ISO 140-8)	33dB
Sound absorption (ISO 354)	0.3 Class D

ENVIRONMENTAL

85% Recycled content cushion backing
11% Recycled content by total product weight
Manufactured using electricity from renewable sources
Carbon Neutral certification
GUT & CRI Green Label Plus certified for indoor air quality
BRE certification – ENP 422

Design Copyright – Milliken & Company

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending.

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.



1096



112721



ENP422




Guarantees:


15 year wear guarantee
Lifetime Antistatic guarantee
Latent Defects guarantee

Installation Method:

Shadowbox - Brick



Scattergraph - Monolithic



Milliken Contract

