



NOTES

1. IT IS THE CLIENTS RESPONSIBILITY TO ENSURE THAT THE STRUCTURE IS CAPABLE OF ACCEPTING THE FIXINGS SHOWN AND SUPPORTING THE DOOR/PRODUCT WEIGHT WHILST AT REST AND DURING OPERATION.

APPROX DOOR WEIGHT = kg

2. CLIENT TO PROVIDE 210 WIDE x 75 DEEP CHASE IN THE FLOOR FOR THE BOTTOM TRACK AND MAKE GOOD AFTER INSTALLATION. CLIENT TO ENSURE FLOOR IS LEVEL IN VICINITY OF DOOR BUNCH.

3. ELECTRICAL DETAILS:
MOTOR TO SUIT 415V 3PH & NEUTRAL 50Hz. SUPPLY. ISOLATOR TO BE PROVIDED WITHIN 1 MTR. OF THE MOTOR BY OTHERS.
MOTOR FULL LOAD CURRENT = 2 AMPS. (APPROX.)

4. LOCKING: CHUBB 7009 PADBAR (PADLOCK BY OTHERS)

5. HANDLES: BOW TYPE INSIDE ONLY

6. FINISH:

Bolton Gate Co. Limited
Waterloo Street
Bolton. BL1 2SP
Telephone: 01204 871000
Facsimile: 01204 871049

TITLE ARRANGEMENT OF ELEC. OPERATED
SUPERFOLD 4000 HIGH SECURITY
FOLDING DOOR (RH)

SITE

DATE

REVISION

CHK'D

REF

DATE

REVISION

CHK'D

REF

SCALE:

1:15(A2)

DRAWN:

F

DATE:

E

CHECKED:

D

WORKS ORDER NUMBER

DRAWING NUMBER