

Interface®

World Woven 890

Product definition

Tapestry Tufted Patterned Structured Loop Tile

Pile Material	100% Recycled Solution Dyed Nylon
Pile Yarn Weight	1017g/m ² ± 5%
Total Weight	4692g/m ² ± 5%
Pile Height	3.8 ± 0.5 mm
Total Thickness	8.2 mm ± 0.5 mm
Gauge/Ends per 10cm	1/10 - 39.4
Tufts per m2	116,230 ± 5%
Backing Type	Graphlex®
Wear Classification	EN 1307 33 Heavy Contract

Radiant panel	(EN ISO 9239/1) Cfl S1 (EN ISO 13501)
Dimensional Stability	≤ 0.2% (ISO 2551 / EN 986)
Impact Sound Insulation (ΔLw)	27 dB (EN ISO 10140-3)
Rating of Sound Absorption	α _w 0.20 (EN ISO 11654)

Sound Absorption

125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz	(EN ISO 354)
0.00	0.06	0.12	0.29	0.38	0.51	α _s

Style number	8113	3m ² - 12 Tiles per Box (25cm x 100cm ± 0.2%)
---------------------	------	--

EN 14041

CE

DOP: 1037/123280

textile floor covering

EN 1307

ASHLAR

HERRINGBONE

33

Cfl-S1

0S

27 dB

0.20

≥ 7

≥ 2.4

DD8BAE5B

www.pro-dit.info

GU

100% GENUINE WOOL

install with TacTiles®

Interface Europe Ltd reserve the right to change or modify specifications

www.interface.com



Mission Zero:
our promise to eliminate any
negative impact our company
may have on the environment
by the year 2020.